

Aqua-Mite

The one and only true
water proofing coating
designed for permanent
under water usage.

Aqua-Mite

- **Aqua-Mite** is a specially formulated two component coating system which can be applied to almost any type of surface for the purpose of water proofing same.
- **Aqua-Mite** consists of a unique blend of hi-tech powders in pack one and in pack two, a very special fluid chemical blend , which, when added to the powders in pack one forms an extremely potent surface coating which can withstand constant water presence.
- **Aqua-Mite** can be used to repair specific leaks in a substrate or for general water proofing.
- **Aqua-Mite** is perfectly safe for use with potable water.

Aqua-mite

- **Aqua-Mite** is environmentally friendly
- **Aqua-Mite** can be used for the following applications:
- Reservoirs (concrete, brick, block, cement plaster, steel etc.)
- Tanks (Asbestos, polypropylene, Polyethylene, Glass fiber etc.)
- Dams
- Retaining walls
- Basements
- Roofs (Flat concrete, Iron, cement fiber, tiled)

Aqua-Mite

- Double wall water proofing
- Floors (Concrete, wood, tilled etc.)
- Decks
- Board walks
- Weather walls
- Damp walls
- Showers
- Bathrooms
- Jacuzzi`s
- Underground structures, canals
- Pipes (Plastic, cement fiber, steel, cement, etc.)

Aqua-Mite

- **Surface preparation**
- The substrate onto which **Aqua-Mite** is to be applied must be clean of loose dirt, dust, grease, grime, old flaky paint etc. The substrate must also be dry.
- In the event of cracks or splits or holes in the substrate, these can be mended with a thicker mixture of **Aqua-Mite** worked into the crack or hole with a spatula and once dry (About 2 hours) can be over coated with **Aqua-Mite** as a paint. A membrane can also be used in conjunction with **Aqua-Mite** for obstinate repairs.

Aqua-Mite

- **Mixture**
- Mix two parts of **Aqua-Mite** fluid with three parts of **Aqua-Mite** powder in a suitable container.
- Stir for a couple of minutes or until all the powder is mixed. **Aqua-Mite** has a pot life of about one hour depending on weather conditions.
- Brushes and equipment can be washed with ordinary tap water, warm and soapy preferably, as the product is miscible in water.

Aqua-Mite

- **Application**
- Apply the mixed **Aqua-Mite** by brush, roller or spray applicator onto the suitably prepared surface. We recommend two coats 24 hours apart and the brush strokes should be at right angles to one another per application.
- In the case of reservoirs or where water is stored, water can be contacted with the **Aqua-Mite** coating after 24 hours, although the **Aqua-Mite** will dry within 30 to 60 minutes.

Aqua-Mite

- **Coverage.**
- **Aqua-Mite** covers approx. 3 square meters per kg.

- **Colours**
- **Aqua-Mite** comes in a variety of colours viz.
- **Blue**
- **Green**
- **Red**
- **Grey**
- **Black**
- **Yellow**

Aqua-Mite

- All the above colours come in light and dark shades. The dark shades cost 20% less than the light shades. (Prices quoted on our price list are for dark colours)
- **Aqua-Mite** is expected to last for a life time under water, baring mechanical damage.
- **Aqua-Mite** is truly a remarkable new age product, very cost effective, easy to use and can turn a novices work into a professional work of art.

Aqua-Mite

- **Cosmo-Dec Everlasting Coatings**
- P. O. Box 1720 Link Hills 3652. Tel. 031 776 3439 or 012 669 0083 Fax. 086 680 7986 or 012 669 0636 e-Mail info@cosmodec.co.za or cosmodec@telkomsa.net
- Plasma fortification string enhancement!
- *Lucrative franchises for manufacturing available in sought after areas, ask for details.*